

MECHANICAL
POWER PRESS



Reckon
Press

ght

Mechanical press



OPEN BACK C FRAME INCLINABLE, NON - INCLINABLE STEEL BODY GEARED & UNGEARED POWER PRESSES.

SPECIFICATIONS

	RN-10	RN-20	RN-30	RN-40	RN-50	RN -65	RN- 80	RN -100	RN -150
	MM	MM	MM	MM	MM	MM	MM	MM	MM
CRANK SHAFT DIAMETER	60	76	89	95	102	111	120	130	140
STROKE ADJUSTMENT	6 TO 51	13 TO 76	13 TO 76	13 TO 82	13 TO 89	13 TO 102	13 TO 115	13 TO 127	13 TO 150
DIST. BED TO RAM (D-1)	203	254	280	318	356	381	406	457	508
BED SIZE (A X B)	381 X 228	483 X 330	533 X 381	585 X 381	660 X 406	711 X 508	762 X 559	864 X 635	1000 X 762
BED THICKNESS (C)	50	64	70	76	83	90	102	102	108
HOLE IN BED	82	95	95	127	152	165	178	203	228
DISTANCE (E)	11	165	190	190	203	254	254	318	381
RAM FACE	2284 X 101	298 X 140	324 X 158	368 X 178	406 X 203	425 X 216	445 X 228	495 X 254	560 X 280
HOLE IN RAM	32	32	38	38	51	51	51	55	63
SIGNLE GEAR (SPM)	80	61	56	52	48	48	40	34	33
DOUBLE GEAR (SPM)	-	57	45	41	40	40	39	36	34
ELE.MOTOR 960 RPM (GEAR)	1 HP	2 HP	3 HP	5	5	7.5	7.5	10	15 HP
ELE.MOTOR 1400 RPM (UNGEAR)	1 HP	2 HP	3 HP	HP	HP	HP	HP	HP	15 HP
FLOOR TO TOP OF BED (D-2)	710	805	813	5813	5813	7.8513	7.9510	10910	910
MACHINE DIMENSION H X L X W	1030 X 710 X 660	2080 X 915 X 740	2190 X 970 X 900	2380 X 1170 X 940	2460 X 1250 X 1120	2640 X 1320 X 1257	3200 X 1300 X 1270	3360 X 1650 X 1400	3500 X 1850 X 1500

*All dimensions are in mm and weight in kg. Approximate only.

*As continuous improvements are contemplated for the product, the design and specification are not binding.

Note : In ungeared machine 960 rpm and in geared / double geared 1440 rpm motor to be used.

All Types of Mechanical Press

Clutch KeySprings

Motor Pulley

Slide Adjusting Spanner (DCX 10 to DCX 150)

Fly Wheel & Gear Guard

Oil Cups For Lubrication Point

Knock-Out System From (10 Ton to 150 Ton)

Die Clamp

OPTIONAL ACCESSORIES

Electrical

Two Hand Operated Clutch

Single / Continuous Stroke

Lubrication Pump (Hand / Motorized)

Tie-Rod

Tommy Bar

Extra Base Plate

Pneumatic Pedal

Inclinable Arrangement From 5 to 30 Ton

Digital Stroke Counter

Feeder, De-Coiler, Straightener

Overload Safety Above 30 Ton

Foundation Pad

Pneumatic Servo Feeder & De-coiler & Straightener





Reckon Press
India
